

Proximity Reader 6630KDM



6630KDM

(Keypad Mifare Reader)

Features

- Supports PIN + CARD credentials.
- OLED display which can be defined
- Company name and Clock on the display
- Smooth attractive design, Elegant.
- Blue LED as normal.
- 1 LED with 2 colors and integral sounder for programming and operation.
- Green connector or cable for wiring.
- Built-in Mifare Reader
- 6630KDM is manufactured in ISO:9001 registered facility.

Description

This superior quality Proximity reader is rugged, weather-resistant and attractive in design. Blue backlit LED assist operation in low or no light conditions. With the internal sounder, 6630KDM provides superior accessibility.

6630KDM can be easily disinfected in areas where hygiene is important, and has an exceptionally long life due to no moving parts. The unit resists the elements such as glue, oil, rain, ice, snow, ideal for hospitals, industrial and commercial application.

This dual-application product has advanced reader features for wide compatibility with different controller types including multiple RFID card transmission formats, LED & Buzzer control.

Specifications

- Maximum read range: 80mm (6.00 in.)
- Modulation: ASK at 13.56M kHz
- Details: U: CPU, Mifare CSN, Mifare Sector
- Card Type: KK1208,M-1,S50,S70 and etc.
- Output: W26/34 Options
- Door Bell: dry contact
- Operating Voltage: 7-12VDC
- Operating Current: $\leq 100\text{mA}$
- Standby Current: $\leq 80\text{mA}$
- Working Temperature: -30°C to 65°C (-22°F to 150°F)
- Operating Humidity: 0 to 95%
- LED Control Input: Dry Contact, Normally Open
- Buzzer Control Input: Dry Contact, Normally Open
- Dimensions: 90mm L x 90mm W x 25mm D