

**6630KH**

(HID Card Reader)

**Features**

- Supports PIN + CARD credentials.
- Smooth attractive design, Elegant.
- Blue LED as normal.
- 1 LED with 2 colors and integral sounder for programming and operation.
- Green connector or cable for wiring.
- Built-in HID Reader
- 6630KH is manufactured in ISO:9001 registered facility.

**Description**

This superior quality Proximity reader is rugged, weather-resistant and attractive in design. Blue backlit LED assist operation in low or no light conditions. With the internal sounder, 6630KH provides superior accessibility.

6630KH can be easily disinfected in areas where hygiene is important, and has an exceptionally long life due to no moving parts. The unit resists the elements such as glue, oil, rain, ice, snow, ideal for hospitals, industrial and commercial application.

This dual-application product has advanced reader features for wide compatibility with different controller types including multiple RFID card transmission formats, LED & Buzzer control.

**Specifications**

- Maximum read range: 80mm (6.00 in.)
- Modulation: ASK at 125 kHz
- Compatible cards: HID compatible.
- Output: W26/34 Options
- Door Bell: dry contact
- Operating Voltage: 7-12VDC
- Operating Current:  $\leq 100\text{mA}$
- Standby Current:  $\leq 80\text{mA}$
- Working Temperature:  $-30^{\circ}\text{C}$  to  $65^{\circ}\text{C}$  ( $-22^{\circ}\text{F}$  to  $150^{\circ}\text{F}$ )
- Operating Humidity: 0 to 95%
- LED Control Input: Dry Contact, Normally Open
- Buzzer Control Input: Dry Contact, Normally Open
- Dimensions: 90mm L x 90mm W x 25mm D
- Weight: 200 g