

**6689LE**

(Long Range Proximity Reader)

**Features**

- Smooth attractive design, with all-weather
- 3 LED indicate power ,pass ,card.
- Supports all EM4100 or Compatible cards.
- 6689LE is manufactured in KEYKING's ISO:9001 registered facility.

**Description**

This superior quality Proximity reader is rugged, weather-resistant and attractive in design. The product was designed to reduce stock levels. Blue backlit LED assist operation in low or no light conditions. With the internal sounder, 6689LE provides superior accessibility.

6689LE can be easily disinfected in areas where hygiene is important, and has an exceptionally long life due to no moving parts. The unit resists the elements such as glue, oil, rain, ice, snow. Ideal for hospital, industrial and commercial application.

This dual-application product has advanced reader features for wide compatibility with different controller types including multiple RFID card transmission formats, LED & Buzzer control.

**Specifications**

- Maximum read range\*: 1200mm (6.00 in.) based on Special 2318-S card
- Modulation: ASK at 125 kHz
- Compatible cards: 26/34 Bits Wiegand EM compatible
- Output: W26/34 Options
- Operating Voltage: 12VDC
- Operating Current:  $\leq 7500\text{mA}$
- Standby Current:  $\leq 500\text{mA}$
- Working Temperature:  $-30^{\circ}\text{C}$  to  $65^{\circ}\text{C}$  ( $-22^{\circ}\text{F}$  to  $150^{\circ}\text{F}$ )
- Operating Humidity: 0 to 95%
- LED Control Input: Dry Contact, Normally Open
- Buzzer Control Input: Dry Contact, Normally Open
- Dimensions: 260mm L x 260mm W x 35mm D
- Weight: 1200 g (0.63 lbs)