

Full Height Turnstile

KK-G15-1



KK-G15-1
(Full Height Turnstile)

Feature:

- The whole system runs smoothly, long-life performance, high operation dependability and fast response, low noise.
- Self-test function, when power on, system restoration automatic.
- Single directional or Bi-directional is selectable.
- LED indicator.
- Automatic reset function: When power off, turnstile will be free to pass, complying with fire safety requirements.

Application

Subway Station, Tourism Sports, Exhibition, Swimming Hall, Residence Area, Enterprise

Specifications

- Assembly: Chassis, movement, control board and power supply
- Housing: Brushed stainless steel, SUS304
- Dimensions: L1630*W1450*H2300mm
- Turntable : One-way/two-way
- Rotate: 120 degree
- Opening time:0.2 seconds
- Central pole: $\phi 102\text{mm}$
- Arm diameter : 38mm*L600mm*3
- The biggest bearing force of the pole : 50KG
- Input:AC220V $\pm 10\%$,50Hz $\pm 4\%$, DC24VDC12V
- Environment: Indoor and outdoor recommended rainproof shed
- Operating temperature: $-10^{\circ}\text{C} \sim 60^{\circ}\text{C}$
- Relative humidity: 5% $\sim 95\%$, no condensation
- Speed:>30 people / minute,
- Aisle Width:550~700mm
- Weight:250kg
- Input interface: Dry contact signal, 12V level or 12V pulse width $\geq 100\text{ms}$
- Communication Interface:RS485 (distance ≤ 1200 meters), TCP/IP
- Life span : Continuous opening and closing more than 8 million times

