



KK-S10
(Swing Gate)

Application

- Office space: business buildings, government agencies, etc.
- Science and education units: universities, research institutes, kindergartens, libraries, museums, etc.
- Commercial service places: supermarkets, business buildings, hotels, banks, convention centers, etc.
- Leisure and entertainment venues: stadiums, parks, scenic spots, playgrounds, leisure clubs, etc.
- Transportation stations: bus stations, railway stations, high-speed rail stations, subway stations, ferries, airports, etc.

Specifications

- Assembly: Chassis, movement, control board and power supply
- Housing: Brushed stainless steel, SUS304
- Dimensions: L1200*W280*H980mm
- Turntable steering: One-way/two-way
- Movement: DC motor
- Opening time: 0.2 seconds
- Input: AC220V \pm 10%, 50Hz \pm 4%, automatically converted to the working voltage of the Turnstile DC24VDC12V
- Environment: Indoor and outdoor recommended rainproof shed
- Operating temperature: -10 $^{\circ}$ C ~ 60 $^{\circ}$ C
- Relative humidity: 5% ~ 95%, no condensation
- Speed: >40 people / minute,
- Aisle Width: 900mm
- Weight: 45kg
- Input interface: Dry contact signal, 12V level or 12V pulse width \geq 100ms
- Communication Interface: RS485 (distance \leq 1200 meters), TCP/IP
- Life span : Continuous opening and closing more than 3 million times

